

RECEIVED
JUN 14 2007
TC 2-2007-1000

1. (Amended) An [A laser capture microdissection] apparatus, comprising:
a transfer film carrier having a substrate surface; and
a laser capture microdissection transfer film coupled to said substrate surface of said transfer film carrier, said laser capture microdissection transfer film including at least one integrally formed structural feature that protrudes and provides a controllable spacing between said laser capture microdissection transfer film and a sample.
2. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film includes a material, that upon exposure to sufficient electromagnetic energy, expands and projects itself away from said substrate surface.
3. (Amended) The [laser capture microdissection] apparatus of claim 1, further comprising a scattering media in proximity to said laser capture microdissection transfer film.
4. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film includes an absorptive substance.
5. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film is hot vacuum baked onto said substrate surface.
6. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film is bonded to said substrate surface with a refractive index matching transparent glue.
7. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said transfer film carrier includes a negative draft such that a distal diameter defined by said surface of said transfer film carrier is greater than a proximal diameter defined by an inner perimeter of said transfer film carrier.

8. (Amended) The [laser capture microdissection] apparatus of claim 7, wherein said transfer film carrier includes a girdle that is contiguous with said negative draft.

9. (Amended) The [laser capture microdissection] apparatus of claim 7, wherein said transfer film carrier includes a chamfer that is contiguous with said substrate surface.

10. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film has a thickness that is less than 500 microns.

11. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film has a thickness that is held to within 20%.

12. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film has a capture surface that is opposite said substrate surface, said capture surface having a flatness that is held within five microns.

13. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film includes at least one pedestal that protrudes and defines a laser capture microdissection acquisition zone.

14. (Amended) The [laser capture microdissection] apparatus of claim 1, wherein said laser capture microdissection transfer film includes a protruding feature that runs along at least three points of a perimeter of said laser capture microdissection transfer film.

15. (Amended) A microcentrifuge tube cap, comprising [the laser capture microdissection apparatus of claim 1]:

a transfer film carrier having a substrate surface; and
a laser capture microdissection transfer film coupled to said substrate surface of said transfer film carrier, said laser capture microdissection transfer film including at least one integrally formed

Cont'd
A1

structural feature that protrudes and provides a controllable spacing between said laser capture microdissection transfer film and a sample.

16. (Amended) An integral portion of a biological reaction vessel, comprising:
a transfer film carrier having a substrate surface; and
a laser capture microdissection transfer film coupled to said substrate surface of said transfer film carrier, wherein said laser capture microdissection transfer film includes at least one integrally formed structural feature that protrudes and provides a controllable spacing between said laser capture microdissection transfer film and a sample.

17. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film includes a material, that upon exposure to sufficient electromagnetic energy, expands and projects itself away from said substrate surface.

18. The integral portion of a biological reaction vessel according to claim 16, further comprising a scattering media in proximity to said laser capture microdissection transfer film.

19. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film includes an absorptive substance.

20. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film is hot vacuum baked onto said substrate surface.

21. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film is bonded to said substrate surface with a refractive index matching transparent glue.

22. The integral portion of a biological reaction vessel according to claim 16, wherein said transfer film carrier includes a negative draft such that a distal diameter defined by said surface of

Contd
A1

said transfer film carrier is greater than a proximal diameter defined by an inner perimeter of said transfer film carrier.

23. The integral portion of a biological reaction vessel according to claim 22, wherein said transfer film carrier includes a girdle that is contiguous with said negative draft.

24. The integral portion of a biological reaction vessel according to claim 22, wherein said transfer film carrier includes a chamfer that is contiguous with said substrate surface.

25. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film has a thickness that is less than 500 microns.

26. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film has a thickness that is held to within 20%.

27. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film has a surface opposite said substrate surface having a flatness that is held within five microns.

28. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film includes at least one pedestal that protrudes and defines a laser capture microdissection acquisition zone.

29. The integral portion of a biological reaction vessel according to claim 16, wherein said laser capture microdissection transfer film includes a protruding feature that runs along at least at least three points of a perimeter of said laser capture microdissection transfer film.

30. (Amended) A microcentrifuge tube cap, comprising [the] an integral portion of a biological reaction vessel [according to claim 16] including

Cont'd
A1

Sub C1

a transfer film carrier having a substrate surface; and
a laser capture microdissection transfer film coupled to said substrate surface of said
transfer film carrier, wherein said laser capture microdissection transfer film includes at least one
integrally formed structural feature that protrudes and provides a controllable spacing between
said laser capture microdissection transfer film and a sample.

31. A laser capture microdissection assembly comprising:
a plate having a top surface; and
at least one laser capture microdissection cap coupled to said top surface of said plate,
wherein said at least one laser capture microdissection cap includes
a transfer film carrier having a substrate surface; and
a laser capture microdissection transfer film coupled to said substrate surface of
said transfer film carrier, wherein said laser capture microdissection transfer film includes at least
one integrally formed structural feature that protrudes and provides a controllable space in
between said laser capture microdissection transfer film and a sample.

32. The laser capture microdissection assembly of claim 31, further comprising a release layer
coated on said plate, said release layer being located between said plate and said laser capture
microdissection transfer film of each of said at least one laser capture microdissection cap.

33. The laser capture microdissection assembly of claim 32, wherein said release layer includes
at least one nonadhesive material selected from the group consisting of silicones and
polytetrafluoroethylenes.

34. The laser capture microdissection assembly of claim 33, wherein said at least one
nonadhesive material is a silicone containing surfactant agent.

35. The laser capture microdissection assembly of claim 31, wherein a plano-concave void is
located between said laser capture microdissection transfer film of said at least one laser capture
microdissection cap and said top surface of said plate.

36. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film includes a transparent thermoplastic.

37. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film includes an absorptive substance.

38. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film is hot vacuum baked onto said substrate surface.

Cont'd
A1
39. The laser capture microdissection assembly of claim 31, wherein said transfer film carrier includes a negative draft such that a distal diameter defined by said surface of said transfer film carrier is greater than a proximal diameter defined by an inner perimeter of said transfer film carrier.

40. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film has a thickness that is less than 500 microns.

41. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film has a thickness that is held to within 20% of a given value.

42. The laser capture microdissection assembly of claim 31, wherein said laser capture microdissection transfer film has a surface opposite said substrate surface having a flatness that is held within five microns.

43. The laser capture microdissection assembly of claim 31, further comprising at least one diffuser coupled to said at least one transfer film carrier.

Sub C2
44. (Amended) A set of microcentrifuge tube caps, comprising [the] a laser capture microdissection assembly [of claim 31] including